

# PVC Tubing

## PVC



### Technical Data

Properties	Typical Values
Material	PVC (Polyvinylchloride)
Operating Temperature (°C)	-15 to 70
Heatshock (°C)	150
Volume Resistivity at 20°C Min (Ω/cm)	2x10 <sup>11</sup>

Complies with SANS 1411 - 1 Type S2 & D3  
Test method SANS 60811

### Dimensions

Product	ID (mm)	Nom.Wall Thickness (mm)
PVC1	1	0.35
PVC2	2	0.35
PVC3	3	0.4
PVC4	4	0.4
PVC5	5	0.4
PVC6	6	0.5
PVC7	7	0.5
PVC8	8	0.5
PVC9	9	0.5
PVC10	10	0.5
PVC11	11	0.5
PVC12	12	0.5
PVC14	14	0.5
PVC16	16	0.7
PVC18	18	0.7
PVC19	19	0.7
PVC20	20	0.7
PVC22	22	0.9
PVC25	25	0.9
PVC28	28	0.9
PVC30	30	0.9
PVC35	35	0.9

### Description

This is a specially formulated polyvinylchloride tubing designed for continuous operation in the -15° to 70°C temperature range. The thin wall makes it suitable for use in any harness & electronic assembly application.

### Features

- Very flexible
- Thin wall thickness
- Colours - Black & white standard, other colours on request
- Standard packaging - 100m reëls
- Can be cut to customer requirements

### Applications

- All harnesses including automotive, slot machines, mining equipment, industrial equipment
- Colour coding of cables

